

Tube Roller

FMX-T6-S Product Description:

- Speed range of 0-70rpm.
- Six roller design for gentle rolling and easy to clean.

FMX-T6-Pro Product Description:

- LCD displays the speed and time.
- Speed range of 10-70rpm.
- Six roller design for gentle rolling and easy to clean.
- Continuous or timer operation.



Tube rollers provide a gentle and highly efficient rolling motions, ideal for mixing blood samples, viscous substances and liquid-solid suspensions. Used in a variety of applications, such as the prevention of blood coagulation, immune precipitation, etc.



FMX-T6-PRO



FMX-T6-S



LCD display



Timer

Parameters /Model	FMX-T6-S	FMX-T6-Pro
Amplitude	24mm	24mm
Motor type	DC motor	DC motor
Rocking motion	Rocking and rolling	Rocking and rolling
Amplitude	24mm	24mm
Max. load capacity	4kg	4kg
Number of rollers	6	6
Roller size [length]	280mm	280mm
Speed range	0 -70rpm	10 -70rpm
Speed display	Scale	LCD
Timer		Yes
Timer display		LCD
Time setting range		1-1199min
Operation mode	Continuous	Continuous/timer
Voltage	100-240V, 50/60Hz	100-240V, 50/60Hz
Power	25W	30W
Dimension [D×W×H]	450×260×120mm	450×260×120mm
Weight	4.5kg	5.1kg
Permissible ambient temperature and humidity	5-40oC,80%RH	5-40oC, 80%RH
Protection class	IP21	IP21