

Pharmacy Refrigerator

FSF-5V656

2~8°C pharmacy refrigerator are specially designed to store medicines,vaccines,regents and bio-medical product



Features

- Accurate Temperature control technology to make the temperature maintain 2~8°C and increment 0.1°C.
- Specially designed forced-air cooling system to ensure frost-free cabinet and good temperature uniformity.
- Designed for ambient temperature 10~32°C with humidity below 95%.
- Three layer toughened glass door with heater to avoid condensation.
- Color spray steel plate inner chamber for friendly using and easy cleaning.
- Wide available voltage range: 187V~242V

Safety

- Safety door lock and controller setting password to prevent unauthorized access.
- Build-in back-up battery to display temperature and to operate audible and visual alarm system for up to 8 hours without AC power.
- Auto on/off cooling fan to prevent cold air from leaking out when the door is opening.
- Visual and audible alarm system: High/low temperature, power failure, sensor error, door ajar
- Power failure protection: turn on delay of the cooling system after power failure.
- Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when controller or two sensor failed.

Humanized design

- 4 casters, and two with stopper for easy moving and fixation.
- 10 adjustable shelves for easy storing.
- Special designed service-free drainage system, ensure no water in the cabinet.
- Auto on/off LED light with manual switch on control panel.

- Automatic spring back design of double heated glass door
- Standard test hole for convenient installation of temperature recorder

Reliable control system: $\pm 3^{\circ}\text{C}$

Forced-air cooling system, frost-free

Glass door with heater, condensation-free

Wide voltage design: 187V~242V available

4 visual and audible alarms

Performance	
Temperature Range	2~8°C
Ambient Temperature	+10~+32°C
Controller	Microprocessor
Display	Digital Display

Refrigeration System	
Compressor	1
Refrigerant	R600a
Cooling Type	Forced air cooling
Defrost Type	Automatic

Electrical Data	
Power Supply(V/Hz)	220/50~60; 115/60
Rated Power(W)	385
Electrical Current(A)	2.3
Power Consumption	5.75 kWh/24h

Alarm	
High/Low Temperature	Y
Sensor Error	Y
Power Failure	Y
Door ajar	Y

Dimensions	
Capacity	656L
Interior Size(W*D*H)	1100*454*1325mm
Exterior Size(W*D*H)	1240*630*1895mm
Package Size(W*D*H)	1335*710*2000mm
N.t./G.t.(approx)	166/184kg
Loading Qty(20'/40'/40'H)	13/27/27

Accessories	
Caster	4
Light	LED
Shelf	10
Temp. Recorder Chart recorder	Optional
Test hole	1/25mm