



Fume Hood



LED Display
Digital LED display: Airflow Level



**Water&Gas Tap
Water Sink**



UV Lamp
Emission of 253.7 nanometers for most efficient decontamination.



Double Layers
1.2mm sheet metal surface, melamine board inward

ADVANTAGE

1. UV Lamp for sterilization.
2. Built-in centrifugal blower.
3. Motorized front glass window.
4. Adjustable air speed: 9 levels.
5. Microprocessor control system, LED display.
6. Double-layer structure: 1.2mm sheet metal surface, melamine board inward.

TECHNICAL PARAMETERS

Model	FSF1000	FSF1200	FSF1500	FSF1800	
External Size (W*D*H)	1000*750*2320mm	1200*800*2345mm	1500*800*2345mm	1800*800*2345mm	
Internal Size (W*D*H)	820*620*750mm	1020*670*750mm	1320*670*750mm	1620*670*750mm	
Work Surface Height	850mm				
Max Opening	520mm	570mm	570mm	570mm	
Air Velocity	0.3~0.8m/s				
Protection Class	Class I				
Protection Type	IP 20				
Noise	≤60dB				
Exhaust Duct	PVC, Standard length: 4 meters. Φ300mm				
Pipe Strap	1 pc				
Fluorescent Lamp	14W*1	21W*1	28W*1	36W*1	
UV Lamp	Emission of 253.7 nanometers for most efficient decontamination				
Blower	Built-in centrifugal blower; Speed adjustable				
Front Window	5mm toughened glass; Motorized; Height adjustable				
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz				
Consumption	400W	400W	500W	500W	
Material	Exterior	Cold-rolled steel with anti-bacteria powder coating.			
	Interior	High grade melamine board with good acid and alkali resistance function			
	Work table	Chemical resistant phenolic resin			
Standard Accessory	UV lamp*2, Fluorescent lamp, Water tap, Gas tap, Water sink, Base cabinet, Pipe strap				
	Total load of 2 waterproof sockets: 500W 4 meters PVC exhaust duct				
Optional Accessory	Active carbon filter				
Gross Weight	272kg	302kg	331kg	366kg	
Package	Main Body	1150*900*1870mm	1350*950*1920mm	1650*950*1890mm	1950*950*1900mm
	Base Cabinet	1150*900*960mm	1350*950*900mm	1650*960*910mm	1950*960*910mm